DOMINANT™
Opto Technologies
Innovating Illumination

DATA SHEET:

SpiceLED™

InGaN S-Spice : SSx-SLD

SpiceLED™

Like spice, its diminutive size is a stark contrast to its standout performance in terms of brightness, durability and reliability. Despite being the smallest in size yet the SpiceLED™ packs a powerful performance and is a highly reliable design device. Its versality enables its application in automotive applicances, key-pad illumination, hand-held devices such as PDAs, notebooks, compact back-lighting applications, consumer appliances, office equipment, audio and video equipment.

Features:

- > High brightness surface mount LED.
- > Super wide viewing angle of 160°.
- > Equivalent to 0603 package outline. Copper lead-frame construction.
- > Qualified according to JEDEC moisture sensitivity Level 2.
- > Compatible to IR reflow soldering.
- > Environmental friendly; RoHS compliance.

Applications:

- > Automotive: interior applications, eg: switches, telematics, climate control system, dashboard, etc.
- > Consumer Appliances: LCD illumination as in PDAs, LCD TV.
- > Communication: indicator and backlight in mobilephone.
- > Display: full color display video notice board.
- > Industrial: white goods (eg: Oven, microwave, etc.).

© 2005 SpiceLED is a trademark of DOMINANT Opto Technologies.
All rights reserved. Product specifications are subject to change without notice.

Optical Characteristics at Tj=25˚C

Part Ordering Number	Color	Viewing Angle°	Luminous Intensity @ 2mA IV (mcd) Min.	Typ.	Max.
SST-SLD-L2N1-1	True Green, 525 nm	160	14.00	22.40	35.50
SSB-SLD-H2K1-1	Blue, 470 nm	160	3.55	5.60	9.00

NOTE
1. All part number above comes in a quantity of 3000 units per reel.
2. Other luminious intensity groups are also available upon request
3. Luminous intensity is measured with an accuracy of ± 11%.
4. Wavelength binning is carried for all units as per the wavelength-binning table. Only one wavelength group is allowed for each reel.

Electrical Characteristics at Tj=25˚C

Part Number	Vf @ If = 2mA Min. (V)	Typ. (V)	Max. (V)	Vf @ If = 10mA Typ. (V)	Vr @ Ir = 10uA Min. (V)
SSx-SLD	2.6	2.8	3.0	3.0	5

Forward voltage, Vf is measured with an accuracy of ± 0.1 V.

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	15	mA
Peak pulse current; (tp ≤ 10μs, Duty cycle = 0.1)	100	mA
Reverse voltage; Ir_{max} = 10μA	5	V
ESD threshold (HBM)	1000	V
LED junction temperature	110	˚C
Operating temperature	-40 … +100	˚C
Storage temperature	-40 … +100	˚C
Power dissipation (at room temperature)	45	mW

Wavelength Grouping at Tj= 25˚C

Color	Group	Wavelength distribution (nm)
SST; True Green	Full	520 - 536
	W	520 - 524
	X	524 - 528
	Y	528 - 532
	Z	532 - 536
SSB; Blue	Full	464 - 476
	W	464 - 468
	X	468 - 472
	Y	472 - 476

Dominant wavelength is measured with an accuracy of ± 1nm .

Luminous Intensity Group at Tj=25˚C

Brightness Group	Luminous Intensity IV (mcd)
H2	3.55 ... 4.50
J1	4.50 ... 5.60
J2	5.60 ... 7.20
K1	7.20 ... 9.00
L2	14.00 ... 18.00
M1	18.00 ... 22.40
M2	22.40 ... 28.50
N1	28.50 ... 35.50

Luminous intensity is measured with an accuracy of ± 11%.

Relative Intensity vs Forward Current (True Green)



Relative Intensity vs Forward Current (Blue)



Forward Current Vs Forward Voltage



Maximum Current VS Ambient Temperature



Relative Intensity Vs Wavelength



Dominant Wavelength Shift Vs Forward Current



Radiation Pattern



SpiceLED™ • InGaN S-Spice : SSx-SLD Package Outlines



Note: The center pad is a common cathode. Please take care during soldering to avoid shorting.

Material

	Material
Lead-frame	Cu Alloy With NiPdAu Plating
Package	High Temperature Resistant Epoxy Resin

Note: product is Pb free

Recommended Solder Pad



Recommended Solder-pad

Alternative Solder-pad
Compatible to ChipLED 0603

Note: Component is based on a new package platform, which features “Bottom Only Terminations“. Solder joints are only formed at the bottom of the component and solder fillet will not be observable as the sides of the component.



Taping and orientation

- Reels come in quantity of 3000 units.
- Reel diameter is 180 mm.



Packaging Specification



Packaging Specification



	Average 1pc SpiceLED	1 completed bag (3000pcs)
Weight (gram)	**0.001**	**140 ± 10**



For SpiceLED™

Cardboard Box Size	Dimensions (mm)	Empty Box Weight (kg)	Reel / Box	Quantity / Box (pcs)
Small	300 x 250 x 250	0.58	15 reels MAX	45,000 MAX
Large	416 x 516 x 476	1.74	55 reels MAX	165,000 MAX

Recommended Pb-free Soldering Profile



Revision History

Page	Subjects	Date of Modification
-	New Format	23 Feb 2006
5	Add Relative Intensity Vs Forward Current Graph	24 Jun 2008
-	Update company name	29 Mar 2010
3, 8	Typo error on Luminous Intensity Update Carrier Tape	13 Feb 2014

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

About Us

DOMINANT Opto Technologies is a dynamic Malaysian Corporation that is among the world's leading SMT LED Manufacturers. An excellence – driven organization, it offers a comprehensive product range for diverse industries and applications. Featuring an internationally certified quality assurance acclaim, DOMINANT's extra bright LEDs are perfectly suited for various lighting applications in the automotive, consumer and communications as well as industrial sectors. With extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing, research and testing capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies can be found on the Internet at http://www.dominant-semi.com.

Please contact us for more information:

DOMINANT Opto Technologies Sdn. Bhd.
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia
Tel: (606) 283 3566 Fax: (606) 283 0566
E-mail: sales@dominant-semi.com

DOMINANT™
Opto Technologies
Innovating Illumination